DECLARATION OF PERFORMANCE No BPA/2023/1

- Unique identification code of the product-type: BPA flat sheet, flat sheet flashings
- Intended use: Roof coverings, internal and external wall and ceiling finishes
- Manufacturer: BALEX METAL Sp. z o.o., ul. Wejherowska 12C, 84-239 Bolszewo
- System of Assessment and Verification of Constancy of Performance: 3
- Harmonised standard: EN 14782:2006

Notified body: Centre Scientifique et Technique du Bâtiment (No 0679), Efectis Nederland BV (No 1234)

6. Declared performances: Table 1

Table 1: Performances

Essential characteristics	Declared performances	
Mechanical strength*)	1,2 kN (spacing of supports ≤ 400 mm)	
Water permeability	Waterproof (no perforations)	
Dimensional change	Thermal expansion coefficient: 12×10-6K-1 (steel) Thermal expansion coefficient: 10,0×10-6 K-1 + 17,0×10-6 K-1 (stainless steel)	
Release of dangerous substances	NPD	
External fire performance*)	Broof (t1), Broof (t2), Broof (t3), Broof (t4)	
Reaction to fire	A2-s1,d0 (PVC(F) coating) A1 (other coatings)	
Durability	Steel grade:	S220GD, S250GD, S280GD, S320GD, 1.4301
	Thickness [mm]:	0,4; 0,5; 0,6; 0,7; 0,75; 0,88; 1,00; 1,25; 1,50; 2,00; 2,50
	Organic coatings (thickness):	PVC(F) (120 μm) SP15 (15 μm) SP25 (25 μm) SP35 (35 μm) Cesar 55 (55 μm)

Designations:

Bolszewo, 07.08.2023

7. Appropriate Technical Documentation or Specific Technical Documentation:

Reference number of the appropriate technical documentation used: BPA/2023/1. Requirements to which the product conforms: p. 5.1 and p. 5.2 EN 14782:2006.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Chief Executive Officer

Marek Dzikiewicz

BALEXMETAL Co To.O. 84-239 Boiszewo, in Wejherowska 120 tel. 58 778-44-44, fax 58 778-44-55 NIP 588-11-30-299 P-191112216

^{*)} for roofing applications only NPD - No Performance Determined